YOUR ENDO TREATMENT USING THE SICAT ACCESSGUIDE

Please note the following workflow to ensure a positive result of your treatment:
















MANUFACTURER

SICAT GMBH & CO. KG BRUNNENALLEE 6 53177 BONN GERMANY WWW.SICAT.COM

SGL@SICAT.COM

ART-NR: 1067011EN DOC-ID: DD33POG002 REVISION: 2019-12-04

YOUR ENDO TREATMENT USING THE SICAT ACCESSGUIDE

Please also observe the following instructions during treatment:



▶ OCCLUSAL HEIGHT

Make sure that there is **enough space** available.

▶ DO NOT LEVER

Always guide the drill **straight** through the drill sleeve without changing the sleeves position.

► WATER COOLING

Perform the drilling under constant cooling.

▶ REVOLUTIONS PER MINUTE

Follow the manufacturer's instructions. SICAT recommends a maximum of 5000 RPM.

► FLUSH THE DRILL PATH

Regularly remove any resulting debris.



FOR COMPLETE PRODUCT INFORMATION, PLEASE USE THE SICAT ACCESSGUIDE INSTRUCTIONS FOR USE.



MANUFACTURER

SICAT GMBH & CO. KG BRUNNENALLEE 6 53177 BONN GERMANY WWW.SICAT.COM

LOCAL SUPPORT

SGL@SICAT.COM

ART-NR: 1067011EN DOC-ID: DD33POG002 REVISION: 2019-12-04